



TECHNICAL DATA SHEET

Oregon Chain Oil

PRODUCT DESCRIPTION

Chain oil with adhesive agent for high-performance motor saws. A very low wear of chains and rails can be guaranteed due to additives which are improving the lubrication.

CHARACTERISTICS

Appearance	dark brown - black, clear
Colour / DIN ISO 2049	D 8.0
Viscosity/40°C / ASTM D 7042	100 mm ² /s
Viscosity index / ASTM D 2270	110
Density/15°C / DIN EN ISO 12185	0,890 g/cm ³
Pour point / DIN ISO 3016	-21 °C
Loading capacity according to Brugger / DIN 51 347	>= 36 N/mm ²
Flash point (Cleveland) / DIN ISO 2592	200 °C

APPLICATION

Oregon Chain Oil offers due to its definitive adhesive strength and the use of wear preventive additives best lubrication of chain saws. Optimal lubrication even under hard conditions of use due to the high performance reserves.

8415BB

05/2019-8415BB-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



ZELLER+GMELIN

TECHNICAL DATA SHEET

Oregon Chain Oil

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

8415BB

05/2019-8415BB-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641